



# Type SOOW UL/CSA

## Portable Cord 600 volt

### #18 AWG - #10 AWG



Cereske Inventory ID#		AWG Size	Num Cond.	No. of Strands	Nom. O.D. Inches	Current Amps†	Approx weight lbs/mft
C01-018-02-BK	*	#18	2	16	0.345	10	65
C01-018-03-BK	*	#18	3	16	0.365	10	80
C01-018-04-BK	*	#18	4	16	0.390	7	94
C01-016-02-BK	*	#16	2	26	0.370	13	77
C01-016-03-BK	*	#16	3	26	0.390	13	94
C01-016-04-BK	*	#16	4	26	0.420	10	114
C01-014-02-BK	*	#14	2	41	0.500	18	154
C01-014-03-BK	*	#14	3	41	0.530	18	171
C01-014-04-BK	*	#14	4	41	0.575	15	209
C01-012-02-BK	*	#12	2	65	0.570	25	168
C01-012-03-BK	*	#12	3	65	0.600	25	223
C01-012-04-BK	*	#12	4	65	0.650	20	276
C01-010-02-BK	*	#10	2	104	0.620	30	230
C01-010-03-BK	*	#10	3	104	0.660	30	289
C01-010-04-BK	*	#10	4	104	0.715	25	351

**Conductors:**

- #18 through #10 AWG fully annealed stranded bare copper

**Insulation:**

- Premium-grade, color coded 90°C EPDM
- Color code: See chart below

**Jacket:**

- Black CPE
- Temperature -40°C to 90°C

**Applications:**

- Portable tools and equipment
- Portable appliances
- Small motors and associated machinery

**Features:**

- Excellent resistance to oil and moisture
- Good tensile strength, elongated and aging characteristics
- High flexibility
- Excellent abrasion resistance
- Water-resistant - suitable for shallow immersion in water if properly sealed and terminated
- UL Listed and CSA Certified for indoor and outdoor use
- Ozone-, sunlight (UV)- and weather-resistant
- MSHA Approved

\* Stocked Item

† Green Conductor for grounding only. Ampacities based on NEC Table 400.5(A)(1) 30°C Ambient Temperature

Cond	Color
2	Black, White
3	Black, White, Green
4	Black, White, Red, Green

More sizes and constructions available.  
 Please see Inventory Page

Note: Information shown is approximate. Each manufacturer's spec may vary slightly and are subject to the manufacturers' tolerances. Contact us for specific manufacturers' technical data.