



# Type SOOW Non-UL Portable Cord 600 volt #8 AWG - #2 AWG



Cereske Inventory ID#	*	AWG Size	Num Cond.	No. of Strands	Nom. O.D. Inches	Current Amps†	Approx weight lbs/mft
C01-008-03-BK	*	#8	3	65	0.695	40	340
C01-008-04-BK	*	#8	4	65	0.760	35	442
C01-008-05-BK	*	#8	5	65	0.840	28	542
C01-006-03-BK	*	#6	3	101	0.790	55	482
C01-006-04-BK	*	#6	4	101	0.865	45	599
C01-006-05-BK	*	#6	5	101	0.945	36	750
C01-004-03-BK	*	#4	3	119	0.925	70	683
C01-004-04-BK	*	#4	4	119	1.015	60	851
C01-004-05-BK	*	#4	5	119	1.115	48	1039
C01-002-03-BK	*	#2	3	133	1.085	95	1003
C01-002-04-BK	*	#2	4	133	1.170	80	1248
C01-002-05-BK	*	#2	5	133	1.390	64	1684

\* Stocked Item

† Green Conductor for grounding only. Ampacities based on NEC Table 400.5(A)(1) 30°C Ambient Temperature

**Conductors:**

- #8 through #2 AWG fully annealed stranded bare copper

**Insulation:**

- Premium-grade, color coded 90°C EPDM
- Color code: See chart below

**Jacket:**

- Black CPE
- Temperature -40°C to 90°C

**Applications:**

- Portable tools and equipment
- Portable appliances
- Small motors and associated machinery

**Features:**

- Excellent resistance to oil and moisture
- Good tensile strength, elongated and aging characteristics
- High flexibility
- Excellent abrasion resistance
- Water-resistant - suitable for shallow immersion in water if properly sealed and terminated
- Ozone-, sunlight (UV)- and weather-resistant
- MSHA Approved

Cond	Color
3	Black, White, Green
4	Black, White, Red, Green
5	Black, White, Red, Orange, Green

More sizes and constructions available.  
 Please see Inventory Page

Note: Information shown is approximate. Each manufacturer's spec may vary slightly and are subject to the manufacturers' tolerances. Contact us for specific manufacturers' technical data.