



CERESKE ELECTRIC CABLE CO., INC.

Stocking Distributor of Electrical Wire and Cable

800-522-9975

Oakland: 510-832-3546

Fax: 510-832-2107

Single Conductor Type W Portable Power Cable 2000 volt

#6 AWG - #500/MCM



Cereske Inventory ID#		AWG Size	No. of Strands	Nom. O.D. Inches	Approx weight lbs/mft
F04-006-01-BK		6	264/30	0.511	200
F04-004-01-BK		4	418/30	0.564	255
F04-002-01-BK	*	2	660/30	0.651	375
F04-001-01-BK		1	836/30	0.729	475
F04-1/0-01-BK		1/0	1056/30	0.751	530
F04-2/0-01-BK	*	2/0	1320/30	0.800	650
F04-3/0-01-BK		3/0	1672/30	0.856	750
F04-4/0-01-BK	*	4/0	2090/30	0.981	970
F04-250-01-BK	*	250	2496/30	1.001	1130
F04-350-01-BK	*	350	3416/30	1.133	1420
F04-500-01-BK	*	500	4880/30	1.255	1913

* Stocked Item

Conductors:

- #6 AWG through 500MCM fully annealed stranded bare copper.

Insulation:

- Color coded 90°C EPR

Cable Reinforcement:

- Open braid reinforcement is applied between the insulation and jacket

Jacket:

- Black CPE
- Temperature -40°C to 90°C

Applications:

- Portable Power Systems
- Entertainment Industry
- Applications that would require temporary power

Features:

- Water-resistant
- Sunlight-resistant
- Withstands exposure to oil, acids, alkalies, heat, flame, moisture
- UL Listed
- MSHA

Note: Information shown is approximate. Each manufacturer's spec may vary slightly and are subject to the manufacturers' tolerances. Contact us for specific manufacturers' technical data.