



Type W

Portable Power Cable 2000 volt

#8 AWG - #500/MCM 2-5 Conductors



Cereske Inventory ID#		AWG Size	Num Cond.	No. of Strands	Nom. O.D. Inches	Approx weight lbs/ mft
P01-008-02-BK		8	2	133	0.770	325
P01-006-02-BK	*	6	2	259	0.910	470
P01-004-02-BK		4	2	259	1.020	620
P01-002-02-BK		2	2	259	1.210	935
P01-001-02-BK		1	2	259	1.370	1305
P01-1/0-02-BK		1/0	2	259	1.435	1555
P01-2/0-02-BK		2/0	2	259	1.555	1860
P01-3/0-02-BK		3/0	2	259	1.670	2230
P01-4/0-02-BK		4/0	2	259	1.815	2655
P01-008-03-BK		8	3	133	0.925	470
P01-006-03-BK		6	3	259	0.995	625
P01-004-03-BK		4	3	259	1.095	810
P01-002-03-BK		2	3	259	1.285	1190
P01-001-03-BK		1	3	259	1.445	1655
P01-1/0-03-BK		1/0	3	259	1.555	1965
P01-2/0-03-BK		2/0	3	259	1.670	2350
P01-3/0-03-BK		3/0	3	259	1.815	2890
P01-4/0-03-BK		4/0	3	259	1.930	3285
P01-250-03-BK		250	3	259	2.390	5070
P01-350-03-BK		350	3	259	2.680	6570
P01-500-03-BK		500	3	259	3.030	8700

* Stocked Item

Continue for more sizes



Conductors:

- #8 AWG through 500kcmil fully annealed stranded bare copper.

Insulation:

- Color coded 90°C EPDM
- Color code: See chart below

Jacket:

- Black CPE
- Temperature -40°C to 90°C

Applications:

- Industrial and light- to medium-duty mining applications
- Heavy-duty service as power supply cable
- Mobile and portable electrical equipment
- Motor and battery leads

Features:

- Withstands severe environmental conditions
- Suitable for immersion in water if properly sealed and terminated
- Withstands exposure to oil, acids, alkalies, heat, moisture and most chemicals
- Rope lay stranding for maximum flex life
- Excellent impact and abrasion resistance
- Sunlight-resistant
- UL Type W
- MSHA

Cond	Color
2	Black, White
3	Black, White, Green
4	Black, White, Red, Green
5	Black, White, Red, Green, Orange

Note: Information shown is approximate. Each manufacturer's spec may vary slightly and are subject to the manufacturers' tolerances. Contact us for specific manufacturers' technical data.



Type W

Portable Power Cable 2000 volt

#8 AWG - #500/MCM 2-5 Conductors



Cereske Inventory ID#		AWG Size	Num Cond.	No. of Strands	Nom. O.D. Inches	Approx weight lbs/ mft
P01-008-04-BK	*	8	4	133	0.980	615
P01-006-04-BK	*	6	4	259	1.070	800
P01-004-04-BK	*	4	4	259	1.210	1040
P01-002-04-BK	*	2	4	259	1.435	1580
P01-001-04-BK	*	1	4	259	1.595	2045
P01-1/0-04-BK	*	1/0	4	259	1.705	2430
P01-2/0-04-BK	*	2/0	4	259	1.845	2950
P01-3/0-04-BK	*	3/0	4	259	1.965	3430
P01-4/0-04-BK	*	4/0	4	259	2.145	3885
P01-250-04-BK		250	4	627	2.610	5579
P01-350-04-BK	*	350	4	888	2.920	7329
P01-500-04-BK		500	4	1221	3.340	9896
P01-008-05-BK	*	8	5	133	1.030	650
P01-006-05-BK	*	6	5	259	1.170	915
P01-004-05-BK	*	4	5	259	1.360	1320
P01-002-05-BK	*	2	5	259	1.595	1925
P01-001-05-BK		1	5	259	1.820	2675
P01-1/0-05-BK	*	1/0	5	259	1.900	2885
P01-2/0-05-BK	*	2/0	5	259	2.060	3630
P01-3/0-05-BK	*	3/0	5	259	2.260	4900
P01-4/0-05-BK	*	4/0	5	259	2.460	5980

* Stocked Item

Conductors:

- #8 AWG through 500kcmil fully annealed stranded bare copper.

Insulation:

- Color coded 90°C EPDM
- Color code: See chart below

Jacket:

- Black CPE
- Temperature -40°C to 90°C

Applications:

- Industrial and light- to medium-duty mining applications
- Heavy-duty service as power supply cable
- Mobile and portable electrical equipment
- Motor and battery leads

Features:

- Withstands severe environmental conditions
- Suitable for immersion in water if properly sealed and terminated
- Withstands exposure to oil, acids, alkalies, heat, moisture and most chemicals
- Rope lay stranding for maximum flex life
- Excellent impact and abrasion resistance
- Sunlight-resistant
- UL Type W
- MSHA

Cond	Color
2	Black, White
3	Black, White, Green
4	Black, White, Red, Green
5	Black, White, Red, Green, Orange

Note: Information shown is approximate. Each manufacturer's spec may vary slightly and are subject to the manufacturers' tolerances. Contact us for specific manufacturers' technical data.