



CERESKE ELECTRIC CABLE CO., INC.

Stocking Distributor of Electrical Wire and Cable

800-522-9975

Oakland: 510-832-3546

Fax: 510-832-2107

Black and Red Welding Cable

Class K Stranding 30 AWG

#6 AWG - #500/MCM



Cereske Inventory ID#	Black	Red	AWG Size	No. of Strands	Nom. O.D. Inches	Approx weight lbs/mft
W01-006-01-xx	*	*	6	259/30	0.380	135
W01-004-01-xx	*	*	4	374/30	0.400	172
W01-002-01-xx	*	*	2	625/30	0.465	260
W01-001-01-xx	*	*	1	778/30	0.495	317
W01-1/0-01-xx	*	*	1/0	990/30	0.560	400
W01-2/0-01-xx	*	*	2/0	1248/30	0.615	487
W01-3/0-01-xx	*	*	3/0	1586/30	0.670	605
W01-4/0-01-xx	*	*	4/0	2054/30	0.750	827
W01-25001-xx	*		250	2496/30	0.830	976
W01-350-01-xx	*		350	3432/30	0.960	1388
W01-500-01-xx	*		500	5054/30	1.200	1995

xx - Black -BK

xx - Red -RD

* Stocked Item

Conductors:

- #6 AWG through 500MCM fully annealed stranded bare copper Class K

Jacket:

- Premium-grade 90°C EPDM, black or red
- Temperature -40°C to 90°C

Applications:

- Secondary voltage resistance welding leads
- Power supply applications not exceeding 600 volts AC
- Leads for motors, generators, batteries

Features:

- Good flexibility
- Abrasion-resistant

Note: Information shown is approximate. Each manufacturer's spec may vary slightly and are subject to the manufacturers' tolerances. Contact us for specific manufacturers' technical data.